

# **FLEXSET**

## **Application Instructions**

A FlexSet Kit Includes:

- 1. Polymer Coated Aggregate**
- 2. 1/2 Gal FlexSet A**
- 3. 1/2 Gal FlexSet B**
- 4. Topping Sand**

### **Packaging & Coverage**

5-Gal **FlexSet Kit** fills 0.4 cubic feet

### **Safety**

**FlexSet** is not a significant skin or eye irritant. Nevertheless, skin or eye contact may lead to sensitization. Appropriate protection is necessary. Gloves and safety glasses are required for handling **FlexSet**. Wash hands before eating, drinking or smoking after handling **FlexSet**.

### **Surface Preparation**

Remove loose & unsound material. Clean and blow out cracks with dry compressed air. Apply only to dry surfaces. Moist surfaces create weak bond. **CAUTION:** Use opened pails right away to avoid moisture contamination.

### **Mixing**

Add all of "A" liquid into . Mix thoroughly with heavy duty mixer (about 1 minute.) Next, add all "B" liquid and mix thoroughly for one minute. Blend is pourable. Working time is approximately eight (8) minutes at 75 °F.

### **Installation**

Squeegee or trowel thin **FlexSet** slurry over repair area. Broadcast topping sand over surface. For deep repairs, place **FlexSet** in lifts topping each lift with aggregate. Installation temperatures are between - 25 °C to 40 °C(-14 °F to 104°F)

### **Cure**

Cure for one hour minimum at 75 °F. before subjecting to traffic. Cold temperatures slow cure. At 55 °F. three hours cure is needed for full traffic. Cold weather cure is accelerated by maintaining **FlexSet** warm prior to application or mixing for an additional 2-3 minutes prior to placement.

### **Shelf Life**

**FLEXSET** shelf life is one year when stored indoor, unopened under cool & dry conditions.

### **Pail Disposal**

Dispose empty pails in accordance with all local, state and federal regulations.

### **First Aid**

**IF INHALED:** Remove to fresh air, if not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen, call a physician. **SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. **EYE CONTACT:** Flush with water, continue for at least 15 minutes. Call a doctor.

### **Spill or Leak**

In case of a liquid spill of unmixed materials A & B absorb spilled material with sawdust or other absorbent, sweep into a waste container, neutralize with decontamination solution(95% water, 5% ammonia, 2% detergent) and store open container outdoors for a minimum of 24 hours. Dispose neutralized waste in accordance with federal, state, and local government environmental regulations.